

DS-K4T108**Value Series Bolt Electric Lock**

- Electric Bolt, 205×34×42mm (8.1×1.3×1.7"), 12VDC, ≤1.2A (Startup Current), 0.2A (Standby)
- Auto-locking if induction module is detected
- Suitable for wooden door, glass door, metal door
- Equipped with internal voltage dependent resistor (MOV)
- Signal output of door lock status (NO\NC\COM)
- Abrasion-proof materials
- Shell is made of aluminum and is hard anodizing electroplated.

▪ Specification

General	
Power supply	12 VDC; ≤ 1.2 A (Startup Current) 0.2 A (Standby)
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working humidity	0 to 95 % (relative humidity)
Dimensions	Lock Body: 205 mm × 34 mm × 42mm (8.1" × 1.3" × 1.7")
Weight	0.74kg (1.6 lb)
Material	Shell: Hard Anodizing Electroplating Operated
Signal output	Dry Contact Output, Max. Voltage 18V. If the wiring is COM/NC, NO Output: Locking; NC Output: Unlocking. If the wiring is COM/No, NC Output: Locking; NO Output: Unlocking;
Delay duration	0/3/6/9s optional
Door type	Wooden Door, glass door, metal Door
Magnetic Lock	
Unlock method	Current Interruption
Surface temperature	≤ Ambient Temperature +10 °C (50 °F)
Suitable door	Wooden Door, Glass Door, and Metal Door

▪ Available Model

DS-K4T108

▪ Accessory

▪ Optional

**DS-K4T108-U1
Value Series Bolt
Electric Lock
Bracket**



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

