

DS-K1103 Pro 1103 Series Card Reader



- M1 card reader
- PC+ABS material shell with PMMA panel design
- Built-in audible beeper
- RS-485 and Wiegand interface
- IP64

▪ Specification

Authentication	
Card reading frequency	13.56MHz
General	
Power supply	12 VDC, ≤ 500 mA
Power consumption	≤ 2 W
Working temperature	-20 °C to 65 °C (-4 °F to 149 °F)
Working humidity	10% to 90% (no condensing)
Dimensions	129 mm × 76 mm × 14.7 mm (5.08" × 2.99" × 0.58")
Installation	Only applied for 120 Gang Box
Weight	≤ 0.15 kg (0.3 lb)
Keypad	DS-K1103M: No keypad DS-K1103MK: Keypad with 12 Keys (0 to 9, *, #)
Buzzer	Support
Function	
ID settings	via DIP Switch

▪ Available Model

DS-K1103M

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq