


DS-K3B631TX-BASE
Fixed Base

- Fixed base for DS-K3B631TX series
- -S for single lane with 2 pedestal , -M for extend more lanes for 1 pedestal.

▪ Specification

General	
Lane width	650mm/750mm/900mm/1100mm
Dimensions	-S: (Without packaging) 650: 1065 mm × 1771 mm × 35 mm 750: 1165 mm × 1771 mm × 35 mm 900: 1315 mm × 1771 mm × 35 mm 1100: 1515 mm × 1771 mm × 35 mm -M: (Without packaging) 650: 934 mm × 1771 mm × 35 mm 750: 1034 mm × 1771 mm × 35 mm 900: 1184 mm × 1771 mm × 35 mm 1100: 1384 mm × 1771 mm × 35 mm
Weight	Reserved
Material	Pedestal installation area: SUS304 Lane: Aluminum plate (with pattern) Framework: Galvanization panel

▪ Maintenance

The main element of the turnstile is stainless steel, which is rustless (antioxidant) and corrosion resistant (The anti corrosion ability in the medium of acid, alkali, and salt). In order to keep the stainless steel from being oxidized or corroded, you should clean and care the turnstile surface periodically .


The instructions and tips for maintaining the turnstile are as follows:

- Select different stainless steel types according to the variety of the environments. You can select 304 stainless steel for common circumstances and 316 stainless steel for the scenarios of seashores and chemical plants.
- Keep the device surface clean and dry.
- Use non-woven cloth and ethyl alcohol to clean the dirt on the device surface.
- Use sourcing pad (do not use mesh cleaning ball) to clean the rust on the device surface by following the wire drawing on the stainless steel. And then use non-woven cloth and stainless steel cleaner to wipe the device surface.
- Clean and maintain the device by using non-woven cloth and stainless steel cleaner periodically. It is suggest to clean the device every month in common circumstances and every week for severe environments (seaside and chemical plants for instance).

▪ Available Model

DS-K3B631TX-BASE650-M,DS-K3B631TX-BASE650-S,DS-K3B631TX-BASE750-M,DS-K3B631TX-BASE750-S,DS-K3B631TX-BASE900-M,DS-K3B631TX-BASE900-S,DS-K3B631TX-BASE1100-M,DS-K3B631TX-BASE1100-S

▪ **Accessory**



DS-K3B631TX
Smart Swing Barrier

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

