



CYBER

Güvenlik & Otomasyon Sistemleri

CYB Ekonomi Serisi 3



The CYB Eco series swing barrier is designed to detect unauthorized entrance or exit. By adopting the swing barrier integrated with the access control system, person should authenticate to pass through the lane via presenting IC or ID card, scanning QR code, etc. It is widely used in attractions, stadiums, construction sites, residences, etc.

Valid passing duration settings: System will cancel the passing permission if a person does not pass through the lane within the valid passing duration
Door remaining open when fire alarm triggered: The barrier will open automatically when alarm is triggered
Barrier will be in free status when powering down

Specification

System	
MCBF	>3 million times
Motor	Brush motor
General	
Throughput	20 to 60 persons per minute The actual throughput is affected by the person passing rate and passing method.
Power supply method	100 to 240 VAC; 50 to 60 Hz
Working temperature	-10 °C to 45 °C (14 °F to 113 °F)
Lane width	600 mm to 1100 mm
Barrier material	Stainless steel pipe; Acrylic glass
Working humidity	10% to 95% (No Condensing)
Pedestal material	SUS304 stainless steel
Dimensions	Without packaging: 1200 mm × 200 mm × 1020 mm (47.2" × 7.9" × 40.2") With packaging: 1408 mm × 348 mm × 1156 mm (55.4" × 13.7" × 45.5")
Application environment	Indoor
Weight	35 kg/38 kg (Left/Right) 77.2 lb/83.8 lb (Left/Right)

Maintenance

The main element of the turnstile is stainless steel, which is rustless (antioxidant) and corrosion resistant (The anti corrosion ability in the medium of acid, alkali, and salt). In order to keep the stainless steel from being oxidized or corroded, you should clean and care the turnstile surface periodically .

The instructions and tips for maintaining the turnstile are as follows:

Select different stainless steel types according to the variety of the environments. You can select 304 stainless steel for common circumstances and 316 stainless steel for the scenarios of seashores and chemical plants.

Keep the device surface clean and dry.

Use non-woven cloth and ethyl alcohol to clean the dirt on the device surface.

Use sourcing pad (do not use mesh cleaning ball) to clean the rust on the device surface by following the wire drawing on the stainless steel. And then use non-woven cloth and stainless steel cleaner to wipe the device surface.

Clean and maintain the device by using non-woven cloth and stainless steel cleaner periodically. It is suggest to clean the device every month in common circumstances and every week for severe environments (seaside and chemical plants for instance).

Dimension

