



# CYBER

Güvenlik & Otomasyon Sistemleri

## CYB Pro Kanatlı 1



The CYB Pro Kanatlı 1 series flap barrier with two barriers and 12 IR lights is designed to detect unauthorized entrance or exit. By adopting the flap barrier integratedly with the access control system, person should authenticate to pass through the lane via swiping IC or ID card, scanning QR code, etc. It is widely used in attractions, stadiums, construction sites, residences, etc.

Self-detection, Self-diagnostics, and automatic alarm .

Audible and visual alarm will be triggered when detecting intrusion, tailgating reverse passing, and climbing over barrier.

TCP/IP network communication: The communication data is specially encrypted to relieve the concern of privacy leak.

LED indicates the entrance/exit and passing status.

Fire alarm passing: When the fire alarm is triggered, the barrier will be open automatically for emergency evacuation.

## Specification

System	MCCB
Motor	> 6 million times
Interface	Servo motor
Network interface	
RS-485	1
RS-232	4
Lock output	4
IO input	2
IO output	2
Capacity	2
Card capacity	
Event capacity	60,000
General	180,000
Throughput	
	30 to 60 persons per minute The actual throughput is affected by the person passing rate and passing method
Power supply method	100 to 240 VAC, 50 to 60 Hz
IR light detectors	12 pairs
Lane width	600 mm (23.62")
Working temperature	-20 °C to 70 °C (-4 °F to 158 °F)
Barrier material	Acrylic glass
Working humidity	0% to 95% (No condensing)
Dimensions	With packaging: 490 mm × 1160 mm × 1640 mm (19.29" × 45.67" × 64.57") Without packaging: 300 mm × 1010 mm × 1406.8 mm (11.81" × 39.76" × 55.38")
Pedestal material	SUS304 stainless steel
Application environment	Indoor and outdoor
Weight	Without packaging: 74 kg (left and right)/90 kg (middle) (163 lb/198 lb) With packaging: 99 kg (left and right)/115 kg (middle) (218 lb/254 lb)
Approval	CE/FCC/CB/RoHS/REACH/WEEE

## Maintenance

The main element of the turnstile is stainless steel, which is rustless (antioxidant) and corrosion resistant (The anti corrosion ability in the medium of acid, alkali, and salt). In order to keep the stainless steel from being oxidized or corroded, you should clean and care the turnstile surface periodically .

The instructions and tips for maintaining the turnstile are as follows:

Select different stainless steel types according to the variety of the environments. You can select 304 stainless steel for common circumstances and 316 stainless steel for the scenarios of seashores and chemical plants.

Keep the device surface clean and dry.

Use non-woven cloth and ethyl alcohol to clean the dirt on the device surface.

Use sourcing pad (do not use mesh cleaning ball) to clean the rust on the device surface by following the wire drawing on the stainless steel. And then use non-woven cloth and stainless steel cleaner to wipe the device surface.

Clean and maintain the device by using non-woven cloth and stainless steel cleaner periodically. It is suggest to clean the