


Perfect Doorphone choice for daily life

The security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. Akuvox's Video Doorphone R20BX2 enables you to easily monitor an entrance door or gate and gives you the peace of mind knowing that your facility is more secure.

***At a Glance***

- Two call buttons with name plate;
- Linux operation system;
- Wide-angle camera: 110° (H), 58° (V);
- Two-way audio communication over IP networks with Echo Cancellation feature;
- Flush-mounted & surface-mounted;
- Complies with SIP & ONVIF;

Physical & Power

- Front panel: Aluminum alloy
- Camera: 2M pixels, automatic lighting
- Buttons: 2
- Light sensor: Support
- Motion sensor: Support
- Wiegand port: Support
- RS485 port: Support
- RF card reader: 13.56MHz & 125kHz, NFC
- Relays out: 2
- Inputs: 2
- Microphone: 1
- Speaker: 1
- Tamper Alarm: Support
- Ethernet port: RJ45, 10/100Mbps adaptive
- 802.3af Power-over-Ethernet
- IP Rating: IP65
- Installation: Flush-mounted or Wall-mounted
- Size: 185x84.5x24mm
- Working Humidity: 10~90%
- Working Temperature: -30°C ~ +60°C
- Storage Temperature: -40°C ~ +70°C

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711μ
- Wideband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

Video

- Sensor: 1/2.8", CMOS
- Pixels: CIF, VGA, 4CIF, 720p, 1080p
- Video codec: H.264
- Video resolution: up to 1920x1080
- Max. image transfer rate: 1080p – 30fps
- Viewing angle: 110°(H) / 58°(V)
- High intensity IR LEDs for picture lighting during dark hours with internal light sensor
- Compatible to 3rd-Party-Video components, e.g. NVRs

Door Entry Feature

- Relays controlled individually by DTMF tones
- Camera permanently operational
- Auto-night mode with LED illumination
- White balance: auto
- Minimum illumination: 0.1LUX

Networking & Protocol

- Protocols support: IPv4, HTTP, HTTPS, FTP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Entry log export
- Access table export / import
- Firmware upgrade
- System logs (include door access logs)

Application Scenario

- Office door phone with on-site or hosted IP-PBX
- Remote site entry over Internet
- Apartment/flat intercom with door access control

Perfect Doorphone choice for daily life

The security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. Akuvox's Video Doorphone R20BX5 enables you to easily monitor an entrance door or gate and gives you the peace of mind knowing that your facility is more secure.

***At a Glance***

- Five call buttons with name plate;
- Linux operation system;
- Wide-angle camera: 110° (H), 58° (V);
- Two-way audio communication over IP networks with Echo Cancellation feature;
- Flush-mounted & surface-mounted;
- Complies with SIP & ONVIF;

Physical & Power

- Front panel: Aluminum alloy
- Camera: 2M pixels, automatic lighting
- Buttons: 5
- Light sensor: Support
- Motion sensor: Support
- Wiegand port: Support
- RS485 port: Support
- RF card reader: 13.56MHz & 125kHz, NFC
- Relays out: 2
- Inputs: 2
- Microphone: 1
- Speaker: 1
- Tamper Alarm: Support
- Ethernet port: RJ45, 10/100Mbps adaptive
- 802.3af Power-over-Ethernet
- IP Rating: IP65
- Installation: Flush-mounted or Wall-mounted
- Size: 185x84.5x24mm
- Working Humidity: 10~90%
- Working Temperature: -30°C ~ +60°C
- Storage Temperature: -40°C ~ +70°C

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711μ
- Wideband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

Video

- Sensor: 1/2.8", CMOS
- Pixels: CIF, VGA, 4CIF, 720p, 1080p
- Video codec: H.264
- Video resolution: up to 1920x1080
- Max. image transfer rate: 1080p – 30fps
- Viewing angle: 110°(H) / 58°(V)
- High intensity IR LEDs for picture lighting during dark hours with internal light sensor
- Compatible to 3rd-Party-Video components, e.g. NVRs

Door Entry Feature

- Relays controlled individually by DTMF tones
- Camera permanently operational
- Auto-night mode with LED illumination
- White balance: auto
- Minimum illumination: 0.1LUX

Networking & Protocol

- Protocols support: IPv4, HTTP, HTTPS, FTP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Entry log export
- Access table export / import
- Firmware upgrade
- System logs (include door access logs)

Application Scenario

- Office door phone with on-site or hosted IP-PBX
- Remote site entry over Internet
- Apartment/flat intercom with door access control

Perfect Doorphone choice for daily life

The security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. Akuvox's Video Doorphone R20BX4 enables you to easily monitor an entrance door or gate and gives you the peace of mind knowing that your facility is more secure.



At a Glance

- Four call buttons with name plate;
- Linux operation system;
- Wide-angle camera: 110° (H), 58° (V);
- Two-way audio communication over IP networks with Echo Cancellation feature;
- Flush-mounted & surface-mounted;
- Complies with SIP & ONVIF;

Physical & Power

- | | |
|--|---|
| • Front panel: Aluminum alloy | • Speaker: 1 |
| • Camera: 2M pixels, automatic lighting | • Tamper Alarm: Support |
| • Buttons: 4 | • Ethernet port: RJ45, 10/100Mbps adaptive |
| • Light sensor: Support | • 802.3af Power-over-Ethernet |
| • Motion sensor: Support | • IP Rating: IP65 |
| • Wiegand port: Support | • Installation: Flush-mounted or Wall-mounted |
| • RS485 port: Support | • Size: 185x84.5x24mm |
| • RF card reader: 13.56MHz & 125kHz, NFC | • Working Humidity: 10~90% |
| • Relays out: 2 | • Working Temperature: -30°C ~ +60°C |
| • Inputs: 2 | • Storage Temperature: -40°C ~ +70°C |
| • Microphone: 1 | |

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711μ
- Wideband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

Video

- Sensor: 1/2.8", CMOS
- Pixels: CIF, VGA, 4CIF, 720p, 1080p
- Video codec: H.264
- Video resolution: up to 1920x1080
- Max. image transfer rate: 1080p – 30fps
- Viewing angle: 110°(H) / 58°(V)
- High intensity IR LEDs for picture lighting during dark hours with internal light sensor
- Compatible to 3rd-Party-Video components, e.g. NVRs

Door Entry Feature

- Relays controlled individually by DTMF tones
- Camera permanently operational
- Auto-night mode with LED illumination
- White balance: auto
- Minimum illumination: 0.1LUX

Networking & Protocol

- Protocols support: IPv4, HTTP, HTTPS, FTP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Entry log export
- Access table export / import
- Firmware upgrade
- System logs (include door access logs)

Application Scenario

- Office door phone with on-site or hosted IP-PBX
- Remote site entry over Internet
- Apartment/flat intercom with door access control

Perfect Doorphone choice for daily life

The security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. Akuvox's Video Doorphone R20BX3 enables you to easily monitor an entrance door or gate and gives you the peace of mind knowing that your facility is more secure.

***At a Glance***

- Three call buttons with name plate;
- Linux operation system;
- Wide-angle camera: 110° (H), 58° (V);
- Two-way audio communication over IP networks with Echo Cancellation feature;
- Flush-mounted & surface-mounted;
- Complies with SIP & ONVIF;

Physical & Power

- Front panel: Aluminum alloy
- Camera: 2M pixels, automatic lighting
- Buttons: 3
- Light sensor: Support
- Motion sensor: Support
- Wiegand port: Support
- RS485 port: Support
- RF card reader: 13.56MHz & 125kHz, NFC
- Relays out: 2
- Inputs: 2
- Microphone: 1
- Speaker: 1
- Tamper Alarm: Support
- Ethernet port: RJ45, 10/100Mbps adaptive
- 802.3af Power-over-Ethernet
- IP Rating: IP65
- Installation: Flush-mounted or Wall-mounted
- Size: 185x84.5x24mm
- Working Humidity: 10~90%
- Working Temperature: -30°C ~ +60°C
- Storage Temperature: -40°C ~ +70°C

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711μ
- Wideband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

Video

- Sensor: 1/2.8", CMOS
- Pixels: CIF, VGA, 4CIF, 720p, 1080p
- Video codec: H.264
- Video resolution: up to 1920x1080
- Max. image transfer rate: 1080p – 30fps
- Viewing angle: 110°(H) / 58°(V)
- High intensity IR LEDs for picture lighting during dark hours with internal light sensor
- Compatible to 3rd-Party-Video components, e.g. NVRs

Door Entry Feature

- Relays controlled individually by DTMF tones
- Camera permanently operational
- Auto-night mode with LED illumination
- White balance: auto
- Minimum illumination: 0.1LUX

Networking & Protocol

- Protocols support: IPv4, HTTP, HTTPS, FTP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Entry log export
- Access table export / import
- Firmware upgrade
- System logs (include door access logs)

Application Scenario

- Office door phone with on-site or hosted IP-PBX
- Remote site entry over Internet
- Apartment/flat intercom with door access control